

RENTAL PRODUCT COMPARISON



JOHN DEERE

Excavators

DEERE	Operating Weight	Maximum Digging Depth	Transport Width	CAT	KUBOTA	BOBCAT	TAKEUCHI			
17G	3,790 lb. (1720 kg)	7 ft. 2 in. (2.19 m)	4 ft. 2 in. (1.28 m)	301.7D CR	17U	—	TB216			
26G	5,780 lb. (2620 kg)	8 ft. 6 in. (2.59 m)	4 ft. 11 in. (1.50 m)	302.7D CR	25U	E26	TB230			
30G	6,850 lb. (3105 kg)	9 ft. 2 in. (2.79 m)	5 ft. 1 in. (1.55 m)	302.7D CR	25U	E26	TB230			
35G	7,760 lb. (3520 kg)	10 ft. (3.06 m)	5 ft. 9 in. (1.74 m)	303.5E2 CR	35U	E35i	TB235			
50G	10,560 lb. (4790 kg)	11 ft. 7 in. (3.53 m)	6 ft. 7 in. (2.00 m)	305E2 CR	—	E50	—			
60G	13,547 lb. (6145 kg)	12 ft. 4 in. (3.77 m)	6 ft. 7 in. (2.00 m)	305.5E2 CR	KX-057	E63	TB260			
DEERE	Operating Weight	Maximum Digging Depth	Transport Width	CAT	KOMATSU	VOLVO	CASE	KOBELCO	LINK-BELT	JCB
75G	17,952 lb. (8143 kg)	15 ft. 1 in. (4.61 m)	7 ft. 7 in. (2.32 m)	—	PC78US	—	CX75C SR	SK75SR	75 X3	—
85G	19,244 lb. (8729 kg)	14 ft. 10 in. (4.51 m)	7 ft. 3 in. (2.20 m)	308E2 CR SB	PC88MR	ECR88D	CX80C	SK85CS	80 X3	—
130G	31,604–32,134 lb. (14,348–14,589 kg)	19 ft. 9 in. (6.03 m)	8 ft. 10 in. (2.69 m)	313F	—	EC140E	CX130D	—	130 X4	JS131
135G	31,500–33,920 lb. (14,300–15,400 kg)	20 ft. 0 in. (5.98 m)	8 ft. 10 in. (2.69 m)	315F	PC138US	ECR145E	CX145C SR	SK140SRCL	145 X3	—
160G LC	39,526 lb. (17,945 kg)	21 ft. 4 in. (6.49 m)	8 ft. 10 in. (2.69 m)	316F	PC170LC	E160E	CX160D	SK170LC	160 X4	JS145
180G LC	45,170 lb. (20,507 kg)	23 ft. 2 in. (7.07 m)	9 ft. 10 in. (3.00 m)	318F	—	—	—	—	—	JS190
190G W (wheeled)	43,431–45,300 lb. (19,700–20,550 kg)	19 ft. 5 in. (5.93 m)	8 ft. 11 in. (2.73 m)	M318F/320F	—	EW180E	—	—	—	—
210G LC	52,097 lb. (23,631 kg)	21 ft. 11 in. (6.67 m)	10 ft. 6 in. (3.19 m)	320F/323F	PC210LC	EC220E	CX210D	SK210LC	210 X4	JS220
245G LC	56,830 lb. (25,800 kg)	21 ft. 9 in. (6.62 m)	10 ft. 6 in. (3.19 m)	325F	PC228USLC	ECR235E	CX235C SR	SK230SRCL	235 X3	—
250G LC	56,100 lb. (25,463 kg)	25 ft. (7.61 m)	11 ft. 1 in. (3.39 m)	326F	PC240LC	EC250E	CX250D	SK260LC	250 X4	—
300G LC	69,223 lb. (31,399 kg)	25 ft. 10 in. (7.87 m)	11 ft. 1 in. (3.39 m)	330F	PC290LC	EC300E	CX300D	SK300LC	300 X4	JS300
345G LC	83,271 lb. (37,771 kg)	24 ft. 10 in. (7.57 m)	11 ft. 1 in. (3.39 m)	330F	PC290LC	EC300E	CX300D	SK300LC	300 X4	—
350G LC	79,655 lb. (36,131 kg)	26 ft. 10 in. (8.18 m)	11 ft. 2 in. (3.39 m)	336F	PC360LC	EC350E	CX350D	SK350LC	350 X4	JS370

Wheel Loaders

DEERE	Loader Dump Clearance	Bucket Capacity	CASE	CAT	VOLVO	KOMATSU
204L	7 ft. 9 in.–8 ft. (2.38–2.43 m)	1.0–1.4 cu. yd. (0.8–1.1 m ³)	21F, 121F	906M	L25H	—
244K-II	8 ft. 3 in.–8 ft. 4 in. (2.51–2.55 m)	1.0–1.4 cu. yd. (0.8–1.1 m ³)	121F, 221F	906M, 907M	L25H, L30G	—
304L	8 ft. 2 in.–8 ft. 7 in. (2.49–2.62 m)	1.0–2.1 cu. yd. (0.8–1.6 m ³)	221F, 321F	907M, 908M	L30G	—
324K	8 ft. 4 in.–10 ft. 4 in. (2.55–3.16 m)	1.0–2.1 cu. yd. (0.8–1.6 m ³)	321F	908M	L35G	—
344L	9 ft. 0 in.–9 ft. 7 in. (2.75–2.92 m)	2.0–2.6 cu. yd. (1.5–2.0 m ³)	—	914M	L45H	—
444K	7 ft. 8 in.–9 ft. 11 in. (2.34–3.03 m)	2.5–4.0 cu. yd. (1.9–3.1 m ³)	521G	918M	L50H	WA200-8
524K-II	8 ft. 2 in.–10 ft. 3 in. (2.50–3.12 m)	2.75–4.0 cu. yd. (2.1–3.1 m ³)	—	926M	L60H	WA250-6
544K-II	7 ft. 10 in.–10 ft. 5 in. (2.40–3.17 m)	3.0–4.5 cu. yd. (2.3–3.4 m ³)	621G	930M	L70H	WA270-8
624K-II	8 ft. 4 in.–10 ft. 7 in. (2.55–3.23 m)	3.5–5.25 cu. yd. (2.7–4.01 m ³)	721G	938M	L90H	WA320-8
644K/644K Hybrid	9 ft. 2 in.–10 ft. 11 in. (2.79–3.33 m)	4.0–4.25 cu. yd. (3.1–3.2 m ³)	821G	950M	L110H	WA380-8
724K	9 ft. 4 in.–10 ft. 11 in. (2.84–3.33 m)	4.0–4.75 cu. yd. (3.1–3.6 m ³)	921G	962M	L120H	—
744K-II	9 ft. 1 in.–11 ft. 10 in. (2.76–3.61 m)	5.25–5.85 cu. yd. (4.0–4.5 m ³)	1021G	966M XE	L150H	WA470-8

Skid Steers

DEERE	Class	Rated Operating Capacity	Gross/Net Power	BOBCAT	CASE	KUBOTA	JCB
—	Under 1,350	—	—	S70*, S450*	SR130*	—	—
312GR*	1,351–1,600 lb.	1,550 lb. (704 kg)	51/48 hp (37.8/35.8 kW)	—	SR160*	—	155*
314G	1,751–2,000 lb.	1,760 lb. (799 kg)	51/48 hp (37.8/35.8 kW)	—	—	—	175
316GR*	1,601–1,750 lb.	1,750 lb. (795 kg)	65/61 hp (48.5/45.6 kW)	S550*	SR175*	—	—
318G	1,751–2,000 lb.	1,945 lb. (883 kg)	65/61 hp (48.5/45.6 kW)	S570	SV185	SSV65	—
320G	2,001–2,200 lb.	2,190 lb. (994 kg)	69/66 hp (51.7/49.4 kW)	S590, S595, S630*	SR210*	—	210*, 215
324G	2,201–2,700 lb.	2,690 lb. (1,221 kg)	74/70 hp (54.8/52.5 kW)	S650, S740	SR240*	SSV75	250*
330G	2,701–3,150 lb.	3,000 lb. (1,362 kg)	91/89 hp (68/66 kW)	S770	SR270*, SV280	—	270, 300
332G	3,151 lb. and over	3,600 lb. (1,634 kg)	100/97 hp (74.6/72 kW)	S850	SV340	—	330

Competitive models are positioned according to rated operating capacity.

*radial lift path

Compact Track Loaders

DEERE	Class	Rated Operating Capacity	Gross/Net Power	BOBCAT	CASE	KUBOTA	TAKEUCHI
—	Under 2,000 lb.	—	—	T450*, T550*	TR270*	—	TL6*
317G	2,001–2,300 lb.	2,125 lb. (965 kg)	65/61 hp (48.5/45.6 kW)	T590, T595, T630*	TR310*	SVL75-2	TL8*
325G	2,301–2,600 lb.	2,590 lb. (1,176 kg)	74/70 hp (54.8/52.5 kW)	T650, T740	TR340*, TV370	—	TL10V2
331G	2,601–3,200 lb.	3,100 lb. (1,407 kg)	91/89 hp (68/66 kW)	T770	TV380	SVL95-2s	TL12R2*
333G	3,201 lb. and over	3,700 lb. (1,680 kg)	100/97 hp (74.6/72 kW)	T870	—	—	TL12V2

Competitive models are positioned according to rated operating capacity.

*radial lift path

Rental Product Comparison

Tractor Loaders

DEERE	Net Peak Power	Operating Weight	Loader Dump Clearance	Loader Bucket Capacity	CASE	CAT	NEW HOLLAND
210L EP	69 hp (51 kW) at 2,010 rpm	10,569 lb. (4794 kg)	8 ft. 9 in. (2.66 m)	112–1.25 cu. yd. (0.86–0.96 m³)	570N EP	415 F2 IL	U80C
210L	93 hp (70 kW) at 2,200rpm	11,326 lb. (5137 kg)	8 ft. 9 in. (2.66 m)	112–1.25 cu. yd. (0.86–0.96 m³)	—	—	—

Backhoes

DEERE	Digging Depth		Loader Dump Clearance	Operating Weight	CASE	CAT	NEW HOLLAND	JCB
	Standard	Extendable						
310L EP	14 ft. 1 in. (4.30 m)	14 ft. 4 in.–17 ft. 10 in. (4.38–5.43 m)	9 ft. 0 in. (2.74 m)	13,822 lb. (6270 kg)	580N EP	415F2	—	3CX
310L	14 ft. 1 in. (4.30 m)	14 ft. 4 in.–17 ft. 10 in. (4.38–5.43 m)	9 ft. 0 in. (2.74 m)	14,669 lb. (6654 kg)	580N	416F2	—	3CX 14
310SL	14 ft. 3 in. (4.34 m)	14 ft. 8 in.–18 ft. 2 in. (4.48–5.53 m)	8 ft. 7 in. (2.62 m)	15,872 lb. (7199 kg)	580SN, 580SN WT	420F2, 420F2-IT	B95C, B95C-TC	3CX 14 Super
310SL HL	—	14 ft. 10 in.–18 ft. 1 in. (4.51–5.52 m)	8 ft. 11 in. (2.73 m)	18,231 lb. (8269 kg)	580SN, 580SN WT	420F2, 420F2-IT	B95C, B95C-TC	3CX 14 Super
315SL	13 ft. 8 in. (4.17 m)	14 ft. 3 in.–17 ft. 8 in. (4.34–5.39 m)	8 ft. 11 in. (2.71 m)	17,554 lb. (7962 kg)	—	—	—	3CX 14 Super
410L	15 ft. 10 in. (4.83 m)	15 ft. 10 in.–19 ft. 8 in. (4.83–5.99 m)	8 ft. 10 in. (2.68 m)	17,786 lb. (8068 kg)	590SN	430F2, 430F2-IT	B110C	—
710L	17 ft. 3 in. (5.26 m)	17 ft. 3 in.–21 ft. 9 in. (5.26–6.63 m)	9 ft. 6 in. (2.89 m)	25,588 lb. (11 607 kg)	—	450F	—	—

Crawler Dozers

DEERE	Operating Weight	Blade Width	Power	CASE	CAT	KOMATSU
450K STD/LGP	17,510–18,752 lb. (7959–8522 kg)	97–124 in. (2464–3150 mm)	80 hp (60 kW)	650L LT/WT/LGP	D3K2 XL/LGP	—
550K STD/LGP	19,758–21,000 lb. (8981–9544 kg)	105–124 in. (2667–3150 mm)	92 hp (69 kW)	750M LT/WT/LGP	D4K2 XL/LGP	D37EX/PX-23, D37EXi/PXi
650K XLT/LGP/SmartGrade™	21,320–22,343 lb. (9691–10 156 kg)	105–128 in. (2667–3251 mm)	104 hp (78 kW)	850M LT/WT/LGP	D5K2 XL/LGP	D39EX/PX-24, D39EXi/PXi-24
700K XLT/LGP/SmartGrade	30,275–31,290 lb. (13 733–14 193 kg)	126–144 in. (3200–3658 mm)	130 hp (97 kW)	1150M LT/WT/LGP	D6K2 XL/LGP / D6K2 Cat Grade-Control 3D	D51EX/PX-22, D51EXi/PXi-22
750K STD/XLT/LGP	34,527–37,745 lb. (15 661–17 121 kg)	128–156 in. (3251–3962 mm)	165 hp (123 kW)	1650M XLT/WT/LGP	D6N XL/LGP	D61EX/PX-24, D61EXi/PXi-24
850K STD/WT/LGP/XLT/WLT	42,558–48,005 lb. (19 304–21 775 kg)	128–168 in. (3251–4267 mm)	205 hp (152 kW)	2050M XLT/WT/LGP	D6T XL/XW/LGP	D65EX/PX/WX-18

Compact Utility Tractors

DEERE	Engine Power	Loader Lift Capacity*	Operating Weight	KUBOTA	MAHINDRA
1023E	22.4 hp (16.5 kW)	681 lb. (309 kg)	1,345 lb. (610 kg)	BX2370, BX2380	eMax22
1025R / 1025R TLB	23.9 hp (17.8 kW)	681 lb. (309 kg)	1,444 lb. (655 kg)	BX2670, BX2680, BX25D	eMax24, eMax25
2025R	24.2 hp (17.8 kW)	882 lb. (400 kg)	1,793 lb. (814 kg)	B2601	Max24, Max26XL
2032R / 2032R TLB	31.2 hp (23.3 kW)	1,356 lb. (615 kg)	2,436 lb. (1,105 kg)	B3350	—
2038R	37.3 hp (27.4 kW)	1,356 lb. (615 kg)	2,436 lb. (1,105 kg)	B3350	—
3025E	24.7 hp (18.4 kW)	1,356 lb. (615 kg)	2,222 lb. (1,008 kg)	L2501	1526
3032E	31.1 hp (28.1 kW)	1,356 lb. (615 kg)	2,222 lb. (1,008 kg)	L3301	1533
3038E	37.7 hp (28.1 kW)	1,356 lb. (615 kg)	2,222 lb. (1,008 kg)	L3901	1538
3033R	32.2 hp (23.7 kW)	2,200 lb. (999 kg)	2,900 lb. (1316 kg)	L3650	1533
3039R	38.7 hp (28.5 kW)	2,200 lb. (999 kg)	2,900 lb. (1316 kg)	L4060	1538, 2540
3046R	45.3 hp (33.3 kW)	2,200 lb. (999 kg)	2,900 lb. (1316 kg)	L4760	2545
4044M	43.1 hp (32.1 kW)	2,500 lb. (1135 kg)	3,770 lb. (1710 kg)	L4701, MX4800	4540 4WD
4044R	43.1 hp (32.1 kW)	2,500 lb. (1135 kg)	3,770 lb. (1710 kg)	L4060	3540
4052M	51.5 hp (37.9 kW)	2,500 lb. (1135 kg)	3,770 lb. (1710 kg)	MX5200	4550 4WD
4052R	51.5 hp (37.9 kW)	2,500 lb. (1135 kg)	3,770 lb. (1710 kg)	L4760, L5460	3550
4066M	65.9 hp (48.5 kW)	2,500 lb. (1135 kg)	3,770 lb. (1710 kg)	MX5800	—
4066R	65.9 hp (48.5 kW)	2,500 lb. (1135 kg)	3,770 lb. (1710 kg)	L6060	—

*Loader measured at full height, at pivot

Gator™ Utility Vehicles

DEERE	Engine Power	Payload Capacity	Speed	POLARIS	KAWASAKI	KUBOTA	CUB CADET	CLUB CAR
TS 2WD	13.5 hp (10.1 kW)	900 lb. (408 kg)	20 mph (32 km/h)	—	Mule SX	RTV400Ci	—	CarryAll 300 Gas
TX 2WD	15.5 hp (11.6 kW)	1,000 lb. (454 kg)	20 mph (32 km/h)	—	Mule SX	RTV500	Volunteer 4x2	CarryAll 550
TH Gas 6x4	15.5 hp (11.6 kW)	1,400 lb. (635 kg)	20 mph (32 km/h)	Sportsman 6x6	—	—	—	CarryAll 1500 Gas
TH Diesel 6x4	18.5 hp (14.0 kW)	1,600 lb. (726 kg)	20 mph (32 km/h)	—	Mule 4010 4x4 Diesel	RTVx900	—	CarryAll 1500 Diesel
HPX615E	21.0 hp (16.0 kW)	1,400 lb. (635 kg)	25 mph (40 km/h)	Ranger 570 EFI	Mule 4010 4x4	RTVx900	Volunteer 4x4/Trail	XRT1550
HPX815E	18.5 hp (14.0 kW)	1,400 lb. (635 kg)	25 mph (40 km/h)	Brutus	Mule 4010 4x4 Diesel	RTVx900	4x4 Trail	XRT1500
XUV 560E	16.0 hp (11.9 kW)	800 lb. (368 kg)	28 mph (45 km/h)	Ranger 500	Mule SX 4x4	RTV500	Challenger 500	XRT1550
XUV 560E S4	16.0 hp (11.9 kW)	1,200 lb. (544 kg)	28 mph (45 km/h)	Ranger Crew 570-4	Mule 4010 Trans 4x4	RTV X1140	Challenger 750 Crew	XRT1550SE
XUV 590E	32.0 hp (23.8 kW)	800 lb. (363 kg)	45 mph (72 km/h)	Ranger 570	Mule 4010 4x4	RTV500	Volunteer 4x4	XRT1550
XUV 590E S4	32.0 hp (23.8 kW)	1,200 lb. (544 kg)	45 mph (72 km/h)	Ranger Crew 570-4	Mule 4010 Trans 4x4	RTV X1140	Challenger 750 Crew	XRT1550SE
XUV825M	50.0 hp (37.0 kW)	1,400 lb. (635 kg)	44 mph (71 km/h)	Ranger 900 XP	Mule Pro-FX	—	—	—
XUV825M S4	50.0 hp (37.0 kW)	1,400 lb. (635 kg)	44 mph (71 km/h)	Ranger 900 Crew	Mule Pro-FXT	—	—	—
XUV855M	23.0 hp (17.0 kW)	1,400 lb. (635 kg)	32 mph (52 km/h)	Ranger Diesel	Mule Pro-DX	RTVx900, X1120D	—	CarryAll 1500
XUV855M S4	23.0 hp (17.0 kW)	1,400 lb. (635 kg)	32 mph (52 km/h)	Ranger Crew Diesel	Mule Pro-DXT	RTV X1140	—	CarryAll 1700

Not all products sold at all dealers. Wherever applicable, specifications are in accordance with SAE standards. Models and specifications subject to change without notice. Competitive models may have changed since the publishing of this comparison.